



# HEARTLAND

ENGINEERED PRODUCTS

**MUST BE FILLED OUT**

**\*Manufacturing Preference:**

Harrison, OH  
Lodi, CA

355 Industrial Drive  
Harrison, OH 45030  
Ph. 800-333-0080  
Ph. 513-367-0080  
Fax 513-367-0081  
[sales@heartland-ep.com](mailto:sales@heartland-ep.com)  
[www.heartland-ep.com](http://www.heartland-ep.com)

## REQUEST FOR PLATFORM QUOTE

*\*Items required to process quote.*

Quote No.: \_\_\_\_\_ Rev: \_\_\_\_\_ Date: \_\_\_\_\_ \*Date Quote Required: \_\_\_\_\_  
 Dealer: \_\_\_\_\_ Address: \_\_\_\_\_  
 City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_ Contact: \_\_\_\_\_  
 Phone: \_\_\_\_\_ Cell: \_\_\_\_\_ Email: \_\_\_\_\_  
 End User: \_\_\_\_\_ \*City: \_\_\_\_\_ \*State: \_\_\_\_\_ Zip: \_\_\_\_\_

Please send CAD file or sketch with this form to: [sales@heartland-ep.com](mailto:sales@heartland-ep.com)

**Platform Usage:** Office Storage Maintenance Other (explain): \_\_\_\_\_

**Quote Type:** Firm (30 days) Budget **Expected Delivery Date:** \_\_\_\_\_

**Layout Drawing Required (PDF):** Yes No

**Dimensions:**

\*Deck Size: \_\_\_\_\_  
 \*Deck Height: \_\_\_\_\_ Critical  
 or  
 \*Clear Height: \_\_\_\_\_ Critical  
 This is clearance under the platform

**\*Live Load Capacity:**

125 PSF 150 PSF 60 PSF Walkway  
 Other: \_\_\_\_\_  
 \*Default live load is 125 PSF

**\*Column Spacing:**

Most Economical  
 Max. Column Load \_\_\_\_\_  
 \*Default: 50,000 lbs unless noted  
 Other: \_\_\_\_\_

**\*Structure Color:**

Gray (Standard)  
 Special Color: \_\_\_\_\_  
 Hot Dip Galvanized (No Paint)

**Guardrail:**

\*Linear Feet of Guardrail/Kickplate: \_\_\_\_\_  
 3 Rail  
 2 Rail  
 Other: \_\_\_\_\_  
 Kickplate: Painted Galvanized

**PE Stamp:** Yes No  
 (if yes) State: \_\_\_\_\_

**Notes:**

**\*Decking:**

- OSB/Corrugated
- Resindek Uncoated/Corrugated  
(FOB Louisville, KY)
- Resindek W/gray Diamond Seal/Corrugated  
(FOB Louisville, KY)
- TRED-eXtra  
(FOB Portland, OR)
- Corrugated only
- Bar Grating
- 12 Ga. Diamond Plate/Corrugated
- ¼" Diamond Plate
- Concrete Ready
- No Deck, Grid Structure Only
- Other \_\_\_\_\_

**\*Pallet Jack:** Yes No  
 Up to 1,250 lbs Up to 2,000 lbs >=2500 lbs  
 If greater than 2,500 lbs please note the maximum weight of fully loaded pallet jack: \_\_\_\_\_

Stair Configuration:	IBC	OSHA		
<b>Qty. by Tread Width</b>	<b>36"</b>	<b>40"</b>	<b>44"</b>	<b>48"</b>
Straight:	—	—	—	—
Straight w/ top landing:	—	—	—	—
U-Shaped:	—	—	—	—
L-Shaped:	—	—	—	—

**Gates:**

Qty. by Width	4'	5'	6'	8'	10'
Swing	—	—	—	—	—
Slide	—	—	—	N/A	—
Pivot	N/A	—	—	—	—

**Ladders: Qty:** \_\_\_\_\_

Steep Ascent Straight (Uncaged) Caged  
 Top Safety Gate Desired? Yes No